



D215 EXHAUST REPAIR PUTTY

PRODUCT DESCRIPTION

- A water based, heat resistant fibrous putty based on inorganic water based binders and heat resistant fillers.
- Designed for use in the repair of exhaust systems for automotive and general industrial applications.
- Heat curing mechanism which provides quick repair times.

AREAS OF USE

- Full exhaust system repair
- Manifolds, Joints and Silencers
- Any high temperature filling repair

PROPERTIES

- Expands and sets quickly under heat.
- Gives a gas tight seal against carbon monoxide (CO) and other dangerous exhaust fumes.
- Vibration resistant
- Asbestos and solvent free

DIRECTIONS FOR USE

- Remove all dirt, grease and loose rust etc.
- Slightly roughen the surface to be filled with suitable abrasive.
- Apply the putty liberally to the repair area with a pallet knife, removing any unnecessary excess.
- Hardening is accelerated by heat from the exhaust system once the engine is running.
- System is sealed once product is hardened.
- All equipment can be cleaned with warm water and detergent.
- Ensure the container is sealed after use.

TECHNICAL DATA	Appearance	Black fibrous thixotropic paste
	pH	13
	Oxidation Resistance	Excellent
	Service Temperature	Up to 1000°C
	Specific Gravity	1.80 - 1.90 @ 20°C
	Slump Resistance	Excellent
	Shelf Life	12 months minimum if kept in cool, dry conditions.

ADHESIVE SEALANTS



PACKAGING • Available in 250gm plastic tubs. Other packs available on request.

HEALTH AND SAFETY • Refer to the relevant Material Safety Data Sheet (MSDS).

ADHESIVE SEALANTS

LEGAL NOTICE

The data contained within this Technical Data Sheet is furnished for information only and is believed to be reliable at the time of issue. We cannot assume responsibility for results obtained by others over whose methods we have no control. It is the responsibility of the customer to determine the products suitability for use. Delta Adhesives Limited accepts no liability arising out of the use of this information or the product described herein.

Delta Adhesives Limited, Units 39 - 41, Claycliffe Business Park, Cannon Way, Barugh Green, Barnsley, S75 1JU
Tel: (01226) 381 571 Fax: (01226) 381 722



www.delta-adhesives.co.uk email: info@delta-adhesives.co.uk



Certificate No. 4997

D215 2/2