

## Section 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product name:** EXHAUST ASSEMBLY PUTTY

**Product code:** D215

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Use of substance / mixture:** Aqueous solution of Sodium silicate blended with fire retardant fillers.

### 1.3. Details of the supplier of the safety data sheet

**Company name:** Delta Adhesives Limited  
Units 39-40  
Claycliffe Business Park  
Cannon Way,  
Barugh Green  
Barnsley,  
S75 1JU

**Tel:** +44 (0) 1226 381 571

**Fax:** +44 (0) 1226 381 722

**Email:** info@delta-adhesives.co.uk

### 1.4. Emergency telephone number

## Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

**Classification under CHIP:** Xi: R36/37/38

**Classification under CLP:** STOT SE 3: H335; Eye Irrit. 2: H319; Skin Irrit. 2: H315

**Most important adverse effects:** Irritating to eyes, respiratory system and skin.

### 2.2. Label elements

**Label elements under CLP:**

**Hazard statements:** H315: Causes skin irritation.

H319: Causes serious eye irritation.

H335: May cause respiratory irritation.

**Signal words:** Warning

**Hazard pictograms:** GHS07: Exclamation mark



**Precautionary statements:** P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.

# SAFETY DATA SHEET

## D215 EXHAUST ASSEMBLY PUTTY

Page: 2

P264: Wash exposed skin thoroughly after handling.  
P271: Use only outdoors or in a well-ventilated area.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P302+352: IF ON SKIN: Wash with plenty of soap and water.  
P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P312: Call a POISON CENTER or doctor if you feel unwell.  
P332+313: If skin irritation occurs: Get medical advice/attention.  
P337+313: If eye irritation persists: Get medical advice/attention.  
P501: Dispose of contents/container to comply with Local, National and International regulations.

### Label elements under CHIP:

**Hazard symbols:** Irritant.



**Risk phrases:** R36/37/38: Irritating to eyes, respiratory system and skin.

**Safety phrases:** S2: Keep out of the reach of children.

S46: If swallowed, seek medical advice immediately and show this container or label.

### 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

SODIUM SILICATE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
2156874	1344-09-8	Xi: R36/37/38	-	10-30%

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

[cont...]

**SAFETY DATA SHEET**  
D215 EXHAUST ASSEMBLY PUTTY

Page: 3

**4.2. Most important symptoms and effects, both acute and delayed**

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

**4.3. Indication of any immediate medical attention and special treatment needed**

**Immediate / special treatment:** Eye bathing equipment should be available on the premises.

**Section 5: Fire-fighting measures**

**5.1. Extinguishing media**

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used.

**5.2. Special hazards arising from the substance or mixture**

**Exposure hazards:** In combustion emits toxic fumes.

**5.3. Advice for fire-fighters**

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

**Section 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

**Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not create dust.

**6.2. Environmental precautions**

**Environmental precautions:** Do not discharge into drains or rivers.

**6.3. Methods and material for containment and cleaning up**

**Clean-up procedures:** Transfer to a closable, labelled salvage container for disposal by an appropriate method.

**6.4. Reference to other sections**

**Reference to other sections:** Refer to section 8 of SDS.

**Section 7: Handling and storage**

**7.1. Precautions for safe handling**

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of dust in the air.

[cont...]

**SAFETY DATA SHEET**  
D215 EXHAUST ASSEMBLY PUTTY

Page: 4

**7.2. Conditions for safe storage, including any incompatibilities**

**Storage conditions:** Store in cool, well ventilated area. Keep container tightly closed.

**Suitable packaging:** Must only be kept in original packaging.

**7.3. Specific end use(s)**

**Specific end use(s):** No data available.

**Section 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Workplace exposure limits:** No data available.

**DNEL/PNEC Values**

**DNEL / PNEC** No data available.

**8.2. Exposure controls**

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency. Respiratory protective device with particle filter.

**Hand protection:** Protective gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

**Section 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

**State:** Paste

**Colour:** Black

**Odour:** Barely perceptible odour

**Evaporation rate:** Negligible

**Solubility in water:** Soluble

**Viscosity:** Viscous

**Relative density:** 1.85

**pH:** 10.5

**9.2. Other information**

**Other information:** No data available.

**Section 10: Stability and reactivity**

**10.1. Reactivity**

**Reactivity:** Stable under recommended transport or storage conditions.

**10.2. Chemical stability**

**Chemical stability:** Stable under normal conditions.

[cont...]

**SAFETY DATA SHEET**  
D215 EXHAUST ASSEMBLY PUTTY

Page: 5

**10.3. Possibility of hazardous reactions**

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.  
Decomposition may occur on exposure to conditions or materials listed below.

**10.4. Conditions to avoid**

**Conditions to avoid:** Heat.

**10.5. Incompatible materials**

**Materials to avoid:** Strong oxidising agents. Strong acids.

**10.6. Hazardous decomposition products**

**Haz. decomp. products:** In combustion emits toxic fumes.

**Section 11: Toxicological information**

**11.1. Information on toxicological effects**

**Relevant effects for mixture:**

Effect	Route	Basis
Irritation	OPT INH DRM	Hazardous: calculated

**Symptoms / routes of exposure**

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

**Section 12: Ecological information**

**12.1. Toxicity**

**Ecotoxicity values:** No data available.

**12.2. Persistence and degradability**

**Persistence and degradability:** Biodegradable.

**12.3. Bioaccumulative potential**

**Bioaccumulative potential:** No bioaccumulation potential.

**12.4. Mobility in soil**

**12.5. Results of PBT and vPvB assessment**

**PBT identification:** This product is not identified as a PBT/vPvB substance.

[cont...]

**SAFETY DATA SHEET**  
D215 EXHAUST ASSEMBLY PUTTY

Page: 6

**12.6. Other adverse effects**

**Other adverse effects:** Negligible ecotoxicity.

**Section 13: Disposal considerations**

**13.1. Waste treatment methods**

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**Section 14: Transport information**

**14.1. UN number**

**UN number:** UN3262

**14.2. UN proper shipping name**

**Shipping name:** CORROSIVE SOLID, BASIC, INORGANIC, N.O.S.  
(SODIUM SILICATE)

**14.3. Transport hazard class(es)**

**Transport class:** 8

**14.4. Packing group**

**Packing group:** I

**14.5. Environmental hazards**

**Environmentally hazardous:** No

**Marine pollutant:** No

**14.6. Special precautions for user**

**Special precautions:** No special precautions.

**Tunnel code:** E

**Transport category:** 1

**Section 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**15.2. Chemical Safety Assessment**

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

**Section 16: Other information**

**Other information**

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

\* indicates text in the SDS which has changed since the last revision.

[cont...]

# SAFETY DATA SHEET

D215 EXHAUST ASSEMBLY PUTTY

Page: 7

**Phrases used in s.2 and s.3:** H315: Causes skin irritation.  
H319: Causes serious eye irritation.  
H335: May cause respiratory irritation.  
R36/37/38: Irritating to eyes, respiratory system and skin.

**Legend to abbreviations:** PNEC = predicted no effect level  
DNEL = derived no effect level  
LD50 = median lethal dose  
LC50 = median lethal concentration  
EC50 = median effective concentration  
IC50 = median inhibitory concentration  
dw = dry weight  
bw = body weight  
cc = closed cup  
oc = open cup  
MUS = mouse  
GPG = guinea pig  
RBT = rabbit  
HAM = hamster  
HMN = human  
MAM = mammal  
PGN = pigeon  
IVN = intravenous  
SCU = subcutaneous  
SKN = skin  
DRM = dermal  
OCC = ocular/corneal  
PCP = physico-chemical properties

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.