

**SAFETY DATA SHEET**  
according to 1907/2006/EC, Article 31

Page 1/8

**D370 Part A PLASTIC WELD Acrylic Adhesive**

Revision 1

Revision date 2019-06-01

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product name	D370 Part A PLASTIC WELD Acrylic Adhesive
--------------	---

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Product Use	[SU3] Industrial uses: Uses of substances as such or in preparations at industrial sites; [PC1] Adhesives, sealants;
-------------	--

**1.3. Details of the supplier of the safety data sheet**

Company	Delta Adhesives Limited
Address	Unit 39-41 Claycliffe Business Park Cannon Way, Barugh Green Barnsley S75 1JU
Web	www.delta-adhesives.co.uk
Telephone	01226 381571
Fax	01226 381722

**1.4. Emergency telephone number**

Emergency telephone number	0044 (0)12260381571
----------------------------	---------------------

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture**

2.1.1. Classification - 1999/45/EC	F; R11 C; R34 Xi; R37-43 R52/53 Symbols: F: Highly flammable. C: Corrosive.
------------------------------------	--

2.1.2. Classification - EC 1272/2008	Flam. Liq. 2: H225; Skin Corr. 1A: H314; Skin Sens. 1: H317; STOT SE 3: H335; Aquatic Chronic 3: H412;
--------------------------------------	--

**2.2. Label elements**

Hazard pictograms	
-------------------	---

**2.3. Other hazards**

Other hazards	This product does not contain any substances classified as PBT or vPvB.
---------------	---

**SECTION 3: Composition/information on ingredients****3.2. Mixtures**

## D370 Part A PLASTIC WELD Acrylic Adhesive

Revision 1

Revision date 2019-06-01

## 3.2. Mixtures

## 67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Methyl methacrylate	607-035-00-6	80-62-6	201-297-1	01-2119452498-28	50 - 60%	F; R11 Xi; R37/38 R43	
2-Methylpropenoic acid (Methacrylic acid)	607-088-00-5	79-41-4	201-204-4	01-2119463884-26	1 - 10%	Xn; R21/22 C; R35	
6,6'-ditert-butyl-4,4'-thiodi-m-cresol (6,6'-Di-tert-butyl-4,4'-thiodi-m-96-6 9-5 -10 -20 cresol)		96-69-5	202-525-2		0 - 0.5%		
Butylated Hydroxytoluene (2,6-Di-tert-butyl-p-cresol)		128-37-0		01-2119555270-46	1 - 10%	Xn; R22 Xi; R37/38 N; R51/53	
Cumene hydroperoxide	617-002-00-8	80-15-9	201-254-7	01-2119475796-19	1 - 10%	O; R7 T; R23 Xn; R21/22-48/20/22 C; R34 N; R51/53	
Hydrocarbon Wax (Paraffin wax, fume)		8002-74-2	232-315-6		0 - 0.5%		

## EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Methyl methacrylate	607-035-00-6	80-62-6	201-297-1	01-2119452498-28		Flam. Liq. 2: H225; STOT SE 3: H335; Skin Irrit. 2: H315; Skin Sens. 1: H317;	
2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, phosphate		52628-03-2	258-053-2			Skin Irrit. 2: H315; Eye Dam. 1: H318;	
Propylidynetrimethanol, ethoxylated, esters with acrylic acid Acrylic Co-Polymer		28961-43-5	500-066-5			Skin Sens. 1: H317; Eye Irrit. 2: H319;	
Triethyleneglycol Dimethacrylate		109-16-0	203-652-6	01-2119969287-21		Skin Sens. 1: H317;	
2-Methylpropenoic acid (Methacrylic acid)	607-088-00-5	79-41-4	201-204-4	01-2119463884-26		Acute Tox. 4: H312; Acute Tox. 4: H302; Skin Corr. 1A: H314;	
trisodecyl phosphite		25448-25-3	246-998-3			Skin Irrit. 2: H315; STOT SE 3: H335;	
Impact Modifier							
ABS Terpolymer							
Para-Toluene Sulfo Chloride		000098-59-9				Met. Corr. 1: H290; Skin Irrit. 2: H315; Eye Dam. 1: H318;	
6,6'-ditert-butyl-4,4'-thiodi-m-cresol (6,6'-Di-tert-butyl-4,4'-thiodi-m-96-6 9-5 -10 -20 cresol)		96-69-5	202-525-2			Skin Sens. 1: H317; Aquatic Chronic 1: H410;	
Butylated Hydroxytoluene (2,6-Di-tert-butyl-p-cresol)		128-37-0		01-2119555270-46		Aquatic Chronic 1: H410;	
Cumene hydroperoxide	617-002-00-8	80-15-9	201-254-7	01-2119475796-19		Org. Perox. EF: H242; Acute Tox. 3: H331; Acute Tox. 4: H312; Acute Tox. 4: H302; STOT RE 2: H373; Skin Corr. 1B: H314; Aquatic Chronic 2: H411;	
Isodecyl diphenyl phosphite		26544-23-0	247-777-4			Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411;	
Defoamer						Flam. Liq. 3: H226; STOT SE 3: H336; Aquatic Chronic 2: H411;	
Wetting & Dispersing Additive						Eye Dam. 1: H318;	
Hydrocarbon Wax (Paraffin wax, fume)		8002-74-2	232-315-6				

## SECTION 4: First aid measures

## 4.1. Description of first aid measures

<b>Inhalation</b>	Move affected person to fresh air at once. Rinse nose and mouth with water. Never give anything by mouth to an unconscious person. Do not induce vomiting. Keep affected person warm and at rest. get medical attention immediately.
-------------------	--

# D370 Part A PLASTIC WELD Acrylic Adhesive

Revision 1

Revision date 2019-06-01

## 4.1. Description of first aid measures

Eye contact	Remove the affected person from the source of contamination immediately. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Immediate medical attention is required.
Skin contact	Remove the affected person from the source of contamination immediately. Remove contaminated clothing. Wash off immediately with plenty of soap and water. Seek medical attention if irritation or symptoms persist.
Ingestion	DO NOT INDUCE VOMITING. Never give anything by mouth to an unconscious person. Rinse mouth thoroughly. Move the exposed person to fresh air. Keep the affected person warm and at rest. If swallowed, seek medical advice immediately and show this container or label.

## 4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Inhalation of vapour may cause shortness of breath.
Eye contact	May cause irritation to eyes. May cause irritation to mucous membranes.
Skin contact	Irritating to skin.
Ingestion	Ingestion causes burns to the respiratory tract.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

	Use as appropriate: Carbon dioxide (CO <sub>2</sub> ), Dry chemical, Foam.
--	--

### 5.2. Special hazards arising from the substance or mixture

	Corrosive. . Burning produces irritating, toxic and obnoxious fumes. Vapour may travel considerable distance to source of ignition and flash back.
--	--

### 5.3. Advice for firefighters

	Self-contained breathing apparatus. Wear protective clothing. In case of fire and/or explosion do not breathe fumes. Control run off water by containing and keeping it out of sewers and watercourses.
--	---

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

	Ensure adequate ventilation of the working area. Evacuate personnel to a safe area. Eliminate all sources of ignition. Wear suitable protective equipment.
--	--

### 6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

### 6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
--	---

### 6.4. Reference to other sections

	Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind, keeping bystanders also upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak side up to prevent escape of liquid.
--	---

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition - No smoking.
--	--

### 7.2. Conditions for safe storage, including any incompatibilities

	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.
--	--

### 7.3. Specific end use(s)

	Industrial use resulting in manufacture of another substance (use of intermediates). Industrial uses:
--	---

## D370 Part A PLASTIC WELD Acrylic Adhesive

Revision 1

Revision date 2019-06-01

## 7.3. Specific end use(s)

Uses of substances as such or in preparations at industrial sites.

## SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

## 8.1.1. Exposure Limit Values

2-Methylpropenoic acid (Methacrylic acid)	WEL 8-hr limit ppm: 20  WEL 15 min limit ppm: 40 WEL 8-hr limit mg/m3 total - inhalable dust: WEL 8-hr limit mg/m3 total - respirable dust:	WEL 8-hr limit mg/m3: 72  WEL 15 min limit mg/m3: 143 WEL 15 min limit mg/m3 total - inhalable dust: WEL 15 min limit mg/m3 total - respirable dust:
6,6'-ditert-butyl-4,4'-thiodi-m-cresol (6,6'-Di-tert-butyl-4,4'-thiodi-m-9 6-69-5 -10 -20 cresol)	WEL 8-hr limit ppm: -  WEL 15 min limit ppm: - WEL 8-hr limit mg/m3 total - inhalable dust: WEL 8-hr limit mg/m3 total - respirable dust:	WEL 8-hr limit mg/m3: 10  WEL 15 min limit mg/m3: 20 WEL 15 min limit mg/m3 total - inhalable dust: WEL 15 min limit mg/m3 total - respirable dust:
Butylated Hydroxytoluene (2,6-Di-tert-butyl-p-cresol)	WEL 8-hr limit ppm: -  WEL 15 min limit ppm: - WEL 8-hr limit mg/m3 total - inhalable dust: WEL 8-hr limit mg/m3 total - respirable dust:	WEL 8-hr limit mg/m3: 10  WEL 15 min limit mg/m3: - WEL 15 min limit mg/m3 total - inhalable dust: WEL 15 min limit mg/m3 total - respirable dust:
Hydrocarbon Wax (Paraffin wax, fume)	WEL 8-hr limit ppm: -  WEL 15 min limit ppm: - WEL 8-hr limit mg/m3 total - inhalable dust: WEL 8-hr limit mg/m3 total - respirable dust:	WEL 8-hr limit mg/m3: 2  WEL 15 min limit mg/m3: 6 WEL 15 min limit mg/m3 total - inhalable dust: WEL 15 min limit mg/m3 total - respirable dust:
Methyl methacrylate	WEL 8-hr limit ppm: 50 WEL 15 min limit ppm: 100 WEL 8-hr limit mg/m3 total - inhalable dust: WEL 8-hr limit mg/m3 total - respirable dust:	WEL 8-hr limit mg/m3: 208 WEL 15 min limit mg/m3: 416 WEL 15 min limit mg/m3 total - inhalable dust: WEL 15 min limit mg/m3 total - respirable dust:

## 8.2. Exposure controls



## 8.2.1. Appropriate engineering controls

Ensure adequate ventilation of the working area.

## 8.2.2. Individual protection measures

Wear chemical protective clothing. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Wash immediately with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes wet or contaminated. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

## Eye / face protection

Approved safety goggles. Face shield. Provide eye wash station.

# D370 Part A PLASTIC WELD Acrylic Adhesive

Revision 1

Revision date 2019-06-01

## 8.2. Exposure controls

Skin protection - Handprotection	Chemical resistant gloves (PVC).
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance	Gel
Colour	White
Odour	Strong
Odour threshold	No data available
pH	No data available
Melting point	No data available
Freezing Point	No data available
Initial boiling point	No data available
Flash point	10 °C
Evaporation rate	No data available
Flammability (solid, gas)	No data available
Vapour pressure	No data available
Vapour density	No data available
Relative density	= 0.98 (H <sub>2</sub> O = 1 @ 20 °C)
Fat Solubility	No data available
Partition coefficient	No data available
Autoignition temperature	No data available
Viscosity	> 500000 mPas (Cone & Plate)
Explosive properties	No data available
Oxidising properties	No data available
Solubility	No data available

### 9.2. Other information

Conductivity	No data available
Gas group	No data available
Benzene Content	Not applicable.
Lead content	Not applicable.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

	Avoid sparks, flames, heat and sources of ignition.
--	---

### 10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

### 10.3. Possibility of hazardous reactions

	Oxidising agents.
--	-------------------

### 10.4. Conditions to avoid

	Heat, sparks and open flames. Do NOT allow to freeze. Keep away from strong acids, alkalis and organic peroxides/hydroperoxides.
--	--

### 10.5. Incompatible materials

	Alkalis. Strong acids. Strong oxidising agents.
--	---

### 10.6. Hazardous decomposition products

	Burning produces irritating, toxic and obnoxious fumes.
--	---

## SECTION 11: Toxicological information

# D370 Part A PLASTIC WELD Acrylic Adhesive

Revision 1  
Revision date 2019-06-01

## 11.1. Information on toxicological effects

Skin corrosion/irritation	Causes burns.
---------------------------	---------------

### 11.1.4. Toxicological Information

6,6'-ditert-butyl-4,4'-thiodi-m-cresol	Oral Rat LD50: 2345mg/kg	Dermal Rabbit LD50: >5010mg/kg
Butylated Hydroxytoluene	Oral Rat LD50: 1700mg/kg Dermal Guinea Pig LD50: >8000mg/kg	Oral Mouse LD50: 800-1600mg/kg
Hydrocarbon Wax	Oral Rat LD50: 15.900,00mg/kg	

### 11.1.13. Other information

	Extensive use of the product in areas with inadequate ventilation may result in the accumulation of hazardous vapour concentrations.
--	--

## SECTION 12: Ecological information

### 12.1. Toxicity

6,6'-ditert-butyl-4,4'-thiodi-m-cresol	Daphnia EC50/48h: 0.1600 mg/l	Green algae EC50/96h: 126mg/l
Butylated Hydroxytoluene	Daphnia EC50/48h: 1.4400 mg/l	

	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
--	---

### 12.2. Persistence and degradability

	The product is potentially degradable.
--	--

### 12.3. Bioaccumulative potential

	No data is available on this product.
--	---------------------------------------

### Partition coefficient

	D370 Part A PLASTIC WELD Acrylic Adhesive	No data available
--	---	-------------------

### 12.4. Mobility in soil

	No data is available on this product.
--	---------------------------------------

### 12.5. Results of PBT and vPvB assessment

	This product does not contain any substances classified as PBT or vPvB.
--	---

### 12.6. Other adverse effects

	May cause long-term adverse effects in the environment.
--	---

## SECTION 13: Disposal considerations

### General information

	Dispose of in compliance with all local and national regulations.
--	---

## SECTION 14: Transport information

### Hazard pictograms

	 
--	---

### 14.1. UN number

	UN2924
--	--------

### 14.2. UN proper shipping name

	FLAMMABLE LIQUID, CORROSIVE, N.O.S.
--	-------------------------------------

## D371 Part A PLASTIC WELD Acrylic Adhesive

Revision 1

Revision date 2019-06-01

## 14.3. Transport hazard class(es)

ADR/RID	3
Subsidiary risk	8
IMDG	3
Subsidiary risk	8
IATA	3
Subsidiary risk	8

## 14.4. Packing group

Packing group	II
---------------	----

## 14.5. Environmental hazards

Environmental hazards	No
Marine pollutant	No

## ADR/RID

Hazard ID	338
Tunnel Category	(D/E)

## IMDG

EmS Code	F-E S-C
----------	---------

## IATA

Packing Instruction (Cargo)	363
Maximum quantity	5 L
Packing Instruction (Passenger)	352
Maximum quantity	1 L

## SECTION 15: Regulatory information

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

	COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC. REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.
--	--

## SECTION 16: Other information

## Other information

Text of risk phrases in Section 3	R7 - May cause fire. R11 - Highly flammable. R21/22 - Harmful in contact with skin and if swallowed. R22 - Harmful if swallowed. R23 - Toxic by inhalation. R34 - Causes burns. R35 - Causes severe burns. R37/38 - Irritating to respiratory system and skin. R43 - May cause sensitisation by skin contact. R48/20/22 - Harmful: danger of serious damage to health by prolonged exposure through inhalation and if swallowed.
-----------------------------------	---

Print date 2019-06-01

# D370 Part A PLASTIC WELD Acrylic Adhesive

Revision 1

Revision date 2019-06-01

## Other information

<b>Text of Hazard Statements in Section 3</b>	R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
	Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. STOT SE 3: H335 - May cause respiratory irritation. Eye Dam. 1: H318 - Causes serious eye damage. Eye Irrit. 2: H319 - Causes serious eye irritation. Acute Tox. 4: H302 - Harmful if swallowed. Acute Tox. 4: H312 - Harmful in contact with skin. Skin Corr. 1A: H314 - Causes severe skin burns and eye damage. Met. Corr. 1: H290 - May be corrosive to metals. Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects. Flam. Liq. 3: H226 - Flammable liquid and vapour. STOT SE 3: H336 - May cause drowsiness or dizziness.

## Further information

	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
--	--