



DST99-103 HIGH BOND BLACK FOAM TAPE

PRODUCT DESCRIPTION

High Performance Double Sided Automotive / Engineering Foam Tape. Designed for panel mounting and construction applications, also for applying body side mouldings and emblems in the automotive sector.

The aggressive solvent acrylic adhesive system means this tape is particularly suited to hostile outdoor environments.

TECHNICAL DATA	Foam thickness	0.8mm
	Foam density	100Kg/m ³
	Foam colour	BLACK
	Liner colour	DARK GREEN
	Liner thickness	80 Micron
	Adhesive	ACRYLIC
	180° Peel Adhesion to stainless steel	820 N/m
	Dynamic Shear Adhesion	75 n/cm ²
	Static Shear Adhesion	25mm x 25mm holds 2kg For 100 hours minimum
	Temperature resistance	-30°C + 90°C
	U.V. light resistance	VERY GOOD

LEGAL NOTICE

The data contained within this Technical Data Sheet is furnished for information only and is believed to be reliable at the time of issue. We cannot assume responsibility for results obtained by others over whose methods we have no control. It is the responsibility of the customer to determine the products suitability for use. Delta Adhesives Limited accepts no liability arising out of the use of this information or the product described herein.

Delta Adhesives Limited, Units 39 - 41, Claycliffe Business Park, Cannon Way, Barugh Green, Barnsley, S75 1JU
 Tel: (01226) 381 571 Fax: (01226) 381 722

TAPES

