

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: D210 TRU-FLEX 4MS Hybrid Sealant Adhesive

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Delta Adhesives Limited
Units 39-40
Claycliffe Business Park
Cannon Way, Barugh Green
Barnsley
South Yorkshire
S75 1JU

Tel: +44 (0) 1226 381571

Fax: +44 (0) 1226 381722

Email: info@delta-adhesives.co.uk

1.4. Emergency telephone number

Emergency tel: +44 1226 381 571 (office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: -: R52/53

Classification under CLP: Eye Irrit. 2: H319; Aquatic Chronic 3: H412; -: EUH208

Most important adverse effects: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

2.2. Label elements

Label elements under CLP:

Hazard statements: EUH208: Contains bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction.

H319: Causes serious eye irritation.

H412: Harmful to aquatic life with long lasting effects.

Signal words: Warning

Hazard pictograms: GHS07: Exclamation mark



SAFETY DATA SHEET
D210 TRU-FLEX 40MS Hybrid Sealant Adhesive

Page: 2

Precautionary statements: P264: Wash thoroughly after handling.
P273: Avoid release to the environment.
P280: Wear.
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+313: If eye irritation persists: Get medical.
P501: Dispose of to.

Label elements under CHIP:

Hazard symbols: Symbol not required.

Risk phrases: R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases: S29: Do not empty into drains.

Precautionary phrases: Contains bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction.

2.3. Other hazards

PBT: This product is not identified as a PBT substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

3-AMINOPROPYLTRIMETHOXYSILANE (AMMO)

EINECS	CAS	CHIP Classification	CLP Classification	Percent
237-511-5	13822-56-5	Xi: R38; Xi: R41	Skin Irrit. 2: H315; Eye Dam. 1: H318	1-10%

TRIMETHOXY VINYLSILANE

220-449-8	2768-02-7	-: R10; Xn: R20	Acute Tox. 4: H332; Flam. Liq. 3: H226	1-10%
-----------	-----------	-----------------	--	-------

BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE AND METHYL 1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL SEBACATE.

-	-	Sens.: R43; N: R50/53	Skin Sens. 1: H317; Aquatic Acute 1: H400; Aquatic Chronic 1: H410	<1%
---	---	-----------------------	--	-----

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

Inhalation: Consult a doctor.

[cont...]

SAFETY DATA SHEET
D210 TRU-FLEX 40MS Hybrid Sealant Adhesive

Page: 3

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Allow product to solidify and remove it by mechanical means. Remove uncured foam with acetone

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

[cont...]

SAFETY DATA SHEET
D210 TRU-FLEX 40MS Hybrid Sealant Adhesive

Page: 4

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

8.1. DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Paste

Colour: Transparent / Colourless

Odour: Barely perceptible odour

Solubility in water: Insoluble

Viscosity: Highly viscous

Boiling point/range°C: >150

Flash point°C: >93

VOC g/l: 12

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

[cont...]

SAFETY DATA SHEET
D210 TRU-FLEX 40MS Hybrid Sealant Adhesive

Page: 5

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE AND METHYL 1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL SEBACATE.

ORAL	RAT	LD50	3230	mg/kg
------	-----	------	------	-------

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

[cont...]

SAFETY DATA SHEET
D210 TRU-FLEX 40MS Hybrid Sealant Adhesive

Page: 6

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and 3: EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.

H226: Flammable liquid and vapour.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

R10: Flammable.

R20: Harmful by inhalation.

R38: Irritating to skin.

R41: Risk of serious damage to eyes.

R43: May cause sensitisation by skin contact.

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.