



## SAFETY DATA SHEET

### Delta D306 Plastic Stick Epoxy Putty

---

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

---

**1.1. Product identifier** D306 Plastic Stick Epoxy Putty

**Product name** D306

**Product number**

#### **1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Identified uses** Two component epoxy based adhesive.

#### **1.3. Details of the supplier of the safety data sheet**

**Supplier** Delta Adhesives Limited  
Units 39-40, Claycliffe Business Park  
Cannon Way  
Barugh Green, Barnsley  
S75 1JU  
South Yorkshire  
Tel: +44 (0) 1226 381 571  
Fax: +44 (0) 1226 381 722  
email: info@delta-adhesives.co.uk

**Web** www.delta-adhesives.co.uk

#### **1.4. Emergency telephone number**

**Emergency telephone** +44 (0) 1226 381 571 (Mon-Fri 8:30am - 4:00pm)

---

#### SECTION 2: Hazards identification

---

##### **2.1. Classification of the substance or mixture**

###### **Classification**

###### **Physical hazards**

Not Classified

###### **Health hazards**

Skin Irrit. 2 - H315 Skin Sens. 1 - H317

###### **Environmental hazards**

Not Classified

###### **Classification (67/548/EEC or 1999/45/EC)**

Xi; R38. R43

###### **Human health**

May cause skin sensitisation or allergic reactions in sensitive individuals. Irritating to eyes and skin.

##### **2.2. Label elements**

###### **Pictogram**



**Signal word** Warning

**Hazard statements**

## CELMEND PLASTIC Delta D306 Plastic Stick Epoxy Putty

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

### Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/container in accordance with national regulations.

### Contains

2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL

### Supplementary precautionary statements

P264 Wash contaminated skin thoroughly after handling.

### 2.3. Other hazards

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

<b>TALC</b> CAS number: 14807-96-6 EC number: 238-877-9	<b>20-50%</b>
<b>Classification</b> Not Classified	<b>Classification (67/548/EEC or 1999/45/EC)</b> -
<b>TITANIUM DIOXIDE</b> CAS number: 13463-67-7 EC number: 236-675-5 REACH registration number: 01-2119489379-17-XXXX	<b>1-5%</b>
<b>Classification</b> Not Classified	<b>Classification (67/548/EEC or 1999/45/EC)</b> -
<b>2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL</b> CAS number: 90-72-2 EC number: 202-013-9 REACH registration number: 01-2119560597-27-XXXX	<b>1-5%</b>
<b>Classification</b> Acute Tox. 4 - H302 Skin Corr. 1B - H314 Skin Sens. 1B - H317 Aquatic Chronic 3 - H412	<b>Classification (67/548/EEC or 1999/45/EC)</b> Xn;R22 Xi;R36/38

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation

Remove affected person from source of contamination. Get medical attention if any discomfort continues.

#### Ingestion

DO NOT induce vomiting. Get medical attention immediately.

#### Skin contact

Wash skin thoroughly with soap and water.

#### Eye contact

Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after washing. Show this Safety Data Sheet to the medical personnel.

### 4.2. Most important symptoms and effects, both acute and delayed

**CELMEND PLASTIC**  
**Delta D306 Plastic Stick Epoxy Putty**

**Inhalation**

No specific symptoms known.

**Ingestion**

May cause discomfort.

**Skin contact**

Causes skin irritation. May cause sensitisation or allergic reactions in sensitive individuals.

**Eye contact**

Irritating to eyes.

**4.3. Indication of any immediate medical attention and special treatment needed**

**Notes for the doctor**

No specific recommendations. If in doubt, get medical attention promptly.

---

**SECTION 5: Firefighting measures**

---

**5.1. Extinguishing media**

**Suitable extinguishing media**

Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.

**Unsuitable extinguishing media**

DO NOT use water if avoidable.

**5.2. Special hazards arising from the substance or mixture**

**Specific hazards**

No unusual fire or explosion hazards noted.

**Hazardous combustion products**

Oxides of carbon. Oxides of nitrogen.

**5.3. Advice for firefighters**

**Protective actions during firefighting**

No specific firefighting precautions known.

**Special protective equipment for firefighters**

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

---

**SECTION 6: Accidental release measures**

---

**6.1. Personal precautions, protective equipment and emergency procedures**

**Personal precautions**

Wear protective clothing as described in Section 8 of this safety data sheet.

**6.2. Environmental precautions**

**Environmental precautions**

Avoid discharge into drains or watercourses or onto the ground.

**6.3. Methods and material for containment and cleaning up**

**Methods for cleaning up**

For waste disposal, see Section 13.

**6.4. Reference to other sections**

**Reference to other sections**

For personal protection, see Section 8. Collect and dispose of spillage as indicated in Section 13.

---

**SECTION 7: Handling and storage**

---

**7.1. Precautions for safe handling**

**Usage precautions**

Avoid contact with skin. Avoid contact with eyes.

## CELMEND PLASTIC Delta D306 Plastic Stick Epoxy Putty

### 7.2. Conditions for safe storage, including any incompatibilities

#### Storage precautions

No special storage precautions required.

### 7.3. Specific end use(s)

#### Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

---

## **SECTION 8: Exposure Controls/personal protection**

---

### 8.1. Control parameters

#### Occupational exposure limits

##### TALC

Long-term exposure limit (8-hour TWA): WEL 1 mg/m3 respirable dust

##### TITANIUM DIOXIDE

Long-term exposure limit (8-hour TWA): WEL 10 mg/m3 inhalable dust

Long-term exposure limit (8-hour TWA): WEL 4 mg/m3 respirable dust

WEL = Workplace Exposure Limit

#### TITANIUM DIOXIDE (CAS: 13463-67-7)

DNEL	Industry - Inhalation; Long term systemic effects: 10 mg/m3 REACH dossier information
PNEC	- Fresh water; 0.127 mg/l - Marine water; 1.0 mg/l - Intermittent release; 0.61 mg/l - STP; 100 mg/l - Sediment (Freshwater); 1000 mg/kg - Sediment (Marinewater); 100 mg/kg - Soil; 100 mg/kg REACH dossier information

#### 2,4,6-TRIS (DIMETHYLAMINOMETHYL)PHENOL (CAS: 90-72-2)

DNEL	Industry - Inhalation; Long term systemic effects: 0.31 mg/m3 Industry - Dermal; Long term systemic effects: 0.2 mg/kg/day
PNEC	- Fresh water; 0.084 mg/l - Marine water; 0.0084 mg/l - Intermittent release; 0.84 mg/l - STP; 0.2 mg/l

### 8.2. Exposure controls

#### Protective equipment



#### Appropriate engineering controls

No specific ventilation requirements.

#### Eye/face protection

Wear eye protection.

#### Hand protection

Wear protective gloves.

#### Hygiene measures

Wash promptly if skin becomes contaminated. Wash hands at the end of each work shift and before eating, smoking and using the toilet.

**CELMEND PLASTIC**  
**Delta D306 Plastic Stick Epoxy Putty**

**Respiratory protection**

No specific recommendations.

**Environmental exposure controls**

Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

---

**SECTION 9: Physical and Chemical Properties**

---

**9.1. Information on basic physical and chemical properties****Appearance**

Solid. Coloured paste.

**Colour**

Blue. White.

**Odour**

Characteristic. Sulphur.

**Odour threshold**

Not determined.

**pH**

Not applicable.

**Melting point**

Not applicable.

**Initial boiling point and range**

>35°C @ 760 mm Hg

**Flash point**

>100°C

**Evaporation rate**

Not applicable.

**Evaporation factor**

Not applicable.

**Flammability (solid, gas)**

Not determined.

**Upper/lower flammability or explosive limits**

Not determined.

**Vapour pressure**

<500 Pa @ 20°C

**Vapour density**

Not applicable.

**Relative density**

1.8

**Bulk density**

Not applicable.

**Solubility(ies)**

Insoluble in water

**Partition coefficient**

Not determined.

**Auto-ignition temperature**

Not determined.

**Decomposition Temperature**

Not determined.

**Viscosity**

**CELMEND PLASTIC**  
**Delta D306 Plastic Stick Epoxy Putty**

Not applicable.

**Explosive properties**

Not applicable.

**9.2. Other information**

---

**SECTION 10: Stability and reactivity**

---

**10.1. Reactivity**

There are no known reactivity hazards associated with this product.

**10.2. Chemical stability**

**Stability**

Stable at normal ambient temperatures and when used as recommended.

**10.3. Possibility of hazardous reactions**

**10.4. Conditions to avoid**

Avoid contact with the following materials: Acids.

**10.5. Incompatible materials**

**Materials to avoid**

Acids. Amines.

**10.6. Hazardous decomposition products**

Oxides of carbon. Oxides of nitrogen.

---

**SECTION 11: Toxicological information**

---

**11.1. Information on toxicological effects**

**Acute toxicity - oral**

**ATE oral (mg/kg)**

16,722.40802676

**Skin sensitisation**

Sensitising.

**Ingestion**

May cause discomfort.

**Skin contact**

Irritating to skin. May cause sensitisation by skin contact.

**Eye contact**

Irritation of eyes and mucous membranes.

**Route of entry**

Skin and/or eye contact.

**CELMEND PLASTIC**  
Delta D306 Plastic Stick Epoxy Putty

**Toxicological information on ingredients.**

**2,4,6-TRIS (DIMETHYLAMINOMETHYL)PHENOL**

**Acute toxicity - oral**

**Acute toxicity oral (LD50 mg/kg)**

2,169

**Species**

Rat

**ATE oral (mg/kg)**

500.0

**Acute toxicity - dermal**

**Acute toxicity dermal (LD50 mg/kg)**

1

**Species**

Rat

---

**SECTION 12: Ecological Information**

---

**12.1. Toxicity**

**Ecological information on ingredients.**

**2,4,6-TRIS (DIMETHYLAMINOMETHYL)PHENOL**

**Acute toxicity - fish**

LC50, 96 hours: 180 - 240 mg/l, Onchorhynchus mykiss (Rainbow trout) LC50, 96 hours: 175 mg/l, Cyprinus carpio (Common carp)

**12.2. Persistence and degradability**

**Persistence and degradability**

The product is not biodegradable.

**12.3. Bioaccumulative potential**

No data available on bioaccumulation.

**Partition coefficient**

Not determined.

**12.4. Mobility in soil**

**Mobility**

The product is insoluble in water and will spread on the water surface. The product is non-volatile. Semi-mobile.

**12.5. Results of PBT and vPvB assessment**

This product does not contain any substances classified as PBT or vPvB.

**12.6. Other adverse effects**

---

**SECTION 13: Disposal considerations**

---

**13.1. Waste treatment methods**

**Disposal methods**

Dispose of waste via a licensed waste disposal contractor.

---

**SECTION 14: Transport information**

---

**General**

The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

**14.1. UN number**

Not applicable.

**CELMEND PLASTIC**  
**Delta D306 Plastic Stick Epoxy Putty**

**14.2. UN proper shipping name**

Not applicable.

**14.3. Transport hazard class(es)**

No transport warning sign required.

**14.4. Packing group**

Not applicable.

**14.5. Environmental hazards****Environmentally hazardous substance/marine pollutant**

No.

**14.6. Special precautions for user**

Not applicable.

**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

---

**SECTION 15: Regulatory information**

---

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU legislation**

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

**Guidance**

Workplace Exposure Limits EH40.

**15.2. Chemical safety assessment**

No chemical safety assessment has been carried out.

---

**SECTION 16: Other information**

---

**Revision comments**

NOTE: Lines within the margin indicate significant changes from the previous revision.

**Revision date** 19/05/2014**Revision** 1**SDS number** 20394**Risk phrases in full**

R22 Harmful if swallowed.  
R36/38 Irritating to eyes and skin.  
R38 Irritating to skin.  
R43 May cause sensitisation by skin contact.

**Hazard statements in full**

H302 Harmful if swallowed.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H412 Harmful to aquatic life with long lasting effects.



**CELMEND PLASTIC**  
Delta D306 Plastic Stick Epoxy Putty

**Disclaimer**

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.