Revision date: 19/05/2014 Revision: 5



SAFETY DATA SHEET Delta D308 Wood Stick Epoxy Putty

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name D308 Wood Stick Epoxy Putty

Product number D308

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Two component epoxy based adhesive.

1.3. Details of the supplier of the safety data sheet

S upplier Delta Adhesives Limited

Units 39-40, Claycliffe Business Park

Cannon Way

Barugh Green, Barnsley

S75 1JU

South Yorkshire

Tel: +44 (0) 1226 381 571 Fax: +44 (0) 1226 381 722

email: in fo@delta-adhesives.co.uk

Web www.delta-adhesives.co.uk

1.4. Emergency telephone number

E mergency telephone +44 (0) 1226 381 571 (Mon-Fri 8:30am - 4:00pm)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards

Not Classified

Health hazards

Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317

Environmental hazards

Aquatic Chronic 3 - H412

Classification (67/548/EEC or 1999/45/EC)

Xi; R36/38. R52/53, R43

Human health

May cause skin sensitisation or allergic reactions in sensitive individuals. Irritating to eyes and skin.

2.2. Label elements

Pictogram



Signal word Warning

Hazard statements

Revision: 5 D308 Wood Stick Epoxy Putty

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P501 Dispose of contents/container in accordance with national regulations.

Contains EPOXY RESIN (Number average MW <= 700), 2,4,6-

TRIS(DIMETHYLAMINOMETHYL)PHENOL

Supplementary precautionary statements

P264 Wash contaminated skin thoroughly after handling.

P337+P313 If eye irritation persists: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

TALC 20-50%

Classification Classification (67/548/EEC or 1999/45/EC)

Not Classified -

EPOXY RESIN (Number average MW <= 700)

20-50%

Classification (67/548/EEC or 1999/45/EC)

Skin Irrit. 2 - H315 R43 Xi;R36/38 N;R51/53

Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411

2,4,6-TRIS (DIMETHYLAMINOMETHYL)PHENOL

1-5%

CAS number: 90-72-2 EC number: 202-013-9 REACH registration number: 01-2119560597-27-XXXX

Classification (67/548/EEC or 1999/45/EC)

Acute Tox. 4 - H302 Xn;R22 Xi;R36/38

Skin Corr. 1B - H314 Skin Sens. 1B - H317 Aquatic Chronic 3 - H412

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove affected person from source of contamination. Get medical attention if any discomfort continues.

Revision: 5 D308 Wood Stick Epoxy Putty

Ingestion

DO NOT induce vomiting. Get medical attention immediately.

Skin contact

Wash skin thoroughly with soap and water.

Eye contact

Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after washing. Show this Safety Data Sheet to the medical personnel.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation

No specific symptoms known.

Ingestion

May cause discomfort.

Skin contact

Causes skin irritation. May cause sensitisation or allergic reactions in sensitive individuals.

Eye contact

Irritating to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor

No specific recommendations. If in doubt, get medical attention promptly.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.

Unsuitable extinguishing media

DO NOT use water if avoidable.

5.2. Special hazards arising from the substance or mixture

Specific hazards

No unusual fire or explosion hazards noted.

Hazardous combustion products

Oxides of carbon. Oxides of nitrogen.

5.3. Advice for firefighters

Protective actions during firefighting

No specific firefighting precautions known.

Special protective equipment for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions

Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions

Avoid discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

For waste disposal, see Section 13.

Revision: 5 D308 Wood Stick Epoxy Putty

6.4. Reference to other sections

Reference to other sections

For personal protection, see Section 8. Collect and dispose of spillage as indicated in Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Avoid contact with skin. Avoid contact with eyes.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

No special storage precautions required.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

TALC

Long-term exposure limit (8-hour TWA): WEL 1 mg/m3 respirable dust

WEL = Workplace Exposure Limit

EPOXY RESIN (Number average MW <= 700) (CAS: 25068-38-6)

DNEL Industry - Inhalation; Long term systemic effects: 12.25 mg/m3

Industry - Inhalation; Short term systemic effects: 12.25 mg/m3 Industry - Dermal; Long term systemic effects: 8.33 mg/kg/day Industry - Dermal; Short term systemic effects: 8.33 mg/kg/day

REACH dossier information

PNEC - Fresh water; 0.006 mg/l

- Marine water; 0.0006 mg/l - Intermittent release; 0.018 mg/l

- STP; 10 mg/l

Sediment (Freshwater); 0.996 mg/kgSediment (Marinewater); 0.0996 mg/kg

- Soil; 0.196 mg/kg

REACH dossier information

2,4,6-TRIS (DIMETHYLAMINOMETHYL)PHENOL (CAS: 90-72-2)

DNEL Industry - Inhalation; Long term systemic effects: 0.31 mg/m3

Industry - Dermal; Long term systemic effects: 0.2 mg/kg/day

PNEC - Fresh water; 0.084 mg/l

Marine water; 0.0084 mg/l
Intermittent release; 0.84 mg/l

- STP; 0.2 mg/l

8.2. Exposure controls

Protective equipment





Appropriate engineering controls

Revision: 5 D308 Wood Stick Epoxy Putty

No specific ventilation requirements.

Eye/face protection

Wear eye protection.

Hand protection

Wear protective gloves.

Hygiene measures

Wash promptly if skin becomes contaminated. Wash hands at the end of each work shift and before eating, smoking and using the toilet.

Respiratory protection

No specific recommendations.

Environmental exposure controls

Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance

Solid. Coloured paste.

Colour

Beige. White.

Odour

Characteristic. Sulphur.

Odour threshold

Not determined.

рΗ

Not applicable.

Melting point

Not applicable.

Initial boiling point and range

>35°C @ 760 mm Hg

Flash point

>100°C

Evaporation rate

Not applicable.

Evaporation factor

Not applicable.

Flammability (solid, gas)

Not determined.

Upper/lower flammability or explosive limits

Not determined.

Vapour pressure

<500 Pa @ 20°C

Vapour density

Not applicable.

Relative density

~ 0.9

Bulk density

Not applicable.

Solubility(ies)

Revision: 5 D308 Wood Stick Epoxy Putty

Insoluble in water

P Matitizaria (so tofficive indi

Not determined.

Auto-ignition temperature

Not determined.

Decomposition Temperature

Not determined.

Viscosity

Not applicable.

Explosive properties

Not applicable.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

There are no known reactivity hazards associated with this product.

10.2. Chemical stability

S tability

Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Avoid contact with the following materials: Acids.

10.5. Incompatible materials

Acids. Amines.

10.6. Hazardous decomposition products

Oxides of carbon. Oxides of nitrogen.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg)

17,241.37931034

Skin sensitisation

Sensitising.

Ingestion

May cause discomfort.

Skin contact

Irritating to skin. May cause sensitisation by skin contact.

Eye contact

Irritation of eyes and mucous membranes.

Route of entry

Skin and/or eye contact.

Revision date: 19/05/2014 Revision: 5 D308 Wood Stick Epoxy Putty

Toxicological information on ingredients.

EPOXY RESIN (Number average MW <= 700)

Acute toxicity - oral

Acute toxicity oral (LD50 mg/kg)

11,400

S pecies

Rat

Acute toxicity - dermal

Acute toxicity dermal (LD50 mg/kg)

1200

S pecies

Rat

2,4,6-TRIS (DIMETHYLAMINOMETHYL)PHENOL

Acute toxicity - oral

Acute toxicity oral (LD50 mg/kg)

2.169

S pecies

Rat

ATE oral (mg/kg)

500.0

Acute toxicity - dermal

Acute toxicity dermal (LD50 mg/kg)

1

S pecies

Rat

SECTION 12: Ecological Information

12.1. Toxicity

Ecological information on ingredients.

EPOXY RESIN (Number average MW <= 700)

Acute toxicity - fish

LC50, 96 hours: 2 mg/l, Onchorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 1.8 mg/l, Daphnia magna

Acute toxicity - aquatic plants

EC₅₀, 72 hours: 11 mg/l, Freshwater algae EC₅₀, 96 hours: 220 mg/l, Scenedesmus subspicatus

Chronic toxicity - aquatic invertebrates

NOEC, 21 days: 0.3 mg/l, Daphnia magna

2,4,6-TRIS (DIMETHYLAMINOMETHYL)PHENOL

Acute toxicity - fish

LC50, 96 hours: 180 - 240 mg/l, Onchorhynchus mykiss (Rainbow trout) LC50, 96 hours: 175 mg/l, Cyprinus carpio (Common carp)

12.2. Persistence and degradability

Persistence and degradability

The product is not biodegradable.

Revision: 5 D308 Wood Stick Epoxy Putty

Ecological information on ingredients.

EPOXY RESIN (Number average MW <= 700)

Biodegradation

-: 28 days

12.3. Bioaccumulative potential

No data available on bioaccumulation.

Partition coefficient

Not determined.

Ecological information on ingredients.

EPOXY RESIN (Number average MW <= 700)

May accumulate in soil and water systems. BCF: 100 - 3000,

Partition coefficient

log Pow: 3.242 Estimated Value

12.4. Mobility in soil

Mobility

The product is insoluble in water and will spread on the water surface. The product is non-volatile. Semi-mobile.

Ecological information on ingredients.

EPOXY RESIN (Number average MW <= 700)

Mobility

Semi-mobile.

Adsorption/desorption coefficient

Soil - Koc: 1800 - 4400 @ °C Estimated Value

Henry's law constant

4.93E-05 Pa m3/mol @ 25°C

12.5. Results of PBT and vPvB assessment

This product does not contain any substances classified as PBT or vPvB.

Ecological information on ingredients.

EPOXY RESIN (Number average MW <= 700)

This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods

Dispose of waste via a licensed waste disposal contractor.

SECTION 14: Transport information

General

The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

Revision date: 19/05/2014 Revision: 5 D308 Wood Stick Epoxy Putty

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MAR POL73/78 and the IBC Code

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

Guidance

Workplace Exposure Limits EH40.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments

NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision date 19/05/2014

Revision

SDS number 20397

Risk phrases in full

R22 Harmful if swallowed.

R36/38 Irritating to eyes and skin.

R43 May cause sensitisation by skin contact.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

Hazard statements in full

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. Revision date: 19/05/2014 Revision: 5 D308 Wood Stick Epoxy Putty

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.