

Delta D350 Fast Black Polyurethane Adhesive Component B

Product code: D350 Component B

Page 1 of 7

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

D350 Fast Black Polyurethane Adhesive Component B

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Adhesives, sealants

Uses advised against

any non-intended use.

1.3. Details of the supplier of the safety data sheet

Company name: Delta Adhesives Limited
Place: Units 39-40 Claycliffe Business Park, Barnsley, S75 1JU, United Kingdom
Telephone: +44 (0)1226 381571
Internet: www.delta-adhesives.co.uk
Responsible Department: info@delta-adhesives.co.uk

1.4. Emergency telephone number: +44 (0)1226 381571 (Mo-Fr, 08:00-16:00)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Directive 67/548/EEC or 1999/45/EC**

This mixture is not classified as hazardous according to Directive 1999/45/EC.

Classification according to Regulation (EC) No. 1272/2008 [CLP]

This mixture is not classified as hazardous according to Regulation (EC) No. 1272/2008.

2.2. Label elements**2.3. Other hazards**

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Further Information**

Product does not contain listed SVHC substances.

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

Remove casualty to fresh air and keep warm and at rest. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

Wash immediately with: Water and soap. In case of skin irritation, consult a physician.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Delta D350 Fast Black Polyurethane Adhesive Component B

Product code: D350 Component B

Page 2 of 7

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. When in doubt or if symptoms are observed, get medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Extinguishing powder, Carbon dioxide (CO₂), Foam, Water spray jet

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Can be released in case of fire: Carbon monoxide., Carbon dioxide (CO₂)

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Avoid contact with skin, eyes and clothes.

Wear personal protection equipment (refer to section 8).

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Wear suitable protective clothing, gloves and eye/face protection. (See section 8.)

Advice on protection against fire and explosion

Usual measures for fire prevention.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place.

Advice on storage compatibility

Do not store together with: Explosives. Oxidizing solids. Oxidizing liquids. Radioactive substances.

Infectious substances.

Delta D350 Fast Black Polyurethane Adhesive Component B

Product code: D350 Component B

Page 3 of 7

Further information on storage conditions

Protect against: Heat, Humidity, UV-radiation/sunlight

7.3. Specific end use(s)

refer to chapter 1.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Additional advice on limit values**

To date, no national critical limit values exist.

8.2. Exposure controls**Appropriate engineering controls**

Provide adequate ventilation.

Protective and hygiene measuresAlways close containers tightly after the removal of product. Wash hands before breaks and after work.
When using do not eat, drink, smoke, sniff.**Eye/face protection**

Recommended eye protection articles: Eye glasses with side protection DIN EN 166

Hand protection

In case of prolonged or frequently repeated skin contact: Wear suitable gloves. DIN EN 374

Suitable material:

CR (polychloroprene, chloroprene rubber) (0,5 mm)

NBR (Nitrile rubber) (0,35 mm)

Butyl caoutchouc (butyl rubber) (0,5 mm)

FKM (fluoro rubber) (0,4 mm)

PVC (Polyvinyl chloride) (0,5 mm)

Breakthrough time (maximum wearing time): >480 min

Check leak tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well.

Skin protection

Protective clothing.

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500.

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	Black
Odour:	characteristic

pH-Value:	not determined
-----------	----------------

Changes in the physical state

Initial boiling point and boiling range:	not determined
--	----------------

Flash point:	not determined
--------------	----------------

Sustaining combustion:	No data available
------------------------	-------------------

Test method

Delta D350 Fast Black Polyurethane Adhesive Component B

Product code: D350 Component B

Page 4 of 7

Explosive properties

none

Lower explosion limits:

not determined

Upper explosion limits:

not determined

Decomposition temperature:

not determined

Oxidizing properties

none

Vapour pressure:

not determined

Density:

not determined

Water solubility:

not determined

Viscosity / dynamic:

not determined

9.2. Other information

Solid content:

not determined

SECTION 10: Stability and reactivity**10.1. Reactivity**

No information available.

10.2. Chemical stability

Stable under normal storage and handling conditions.

10.3. Possibility of hazardous reactions

No information available.

10.4. Conditions to avoid

No information available.

10.5. Incompatible materials

Oxidising agent, strong, Reducing agent, strong, Strong acid, Strong alkali

10.6. Hazardous decomposition productsCan be released in case of fire: Carbon monoxide., Carbon dioxide (CO₂)**SECTION 11: Toxicological information****11.1. Information on toxicological effects****Toxicokinetics, metabolism and distribution**

No information available.

Acute toxicity

Based on available data, the classification criteria are not met.

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

STOT-single exposureBased on available data, the classification criteria are not met.
There are no data available on the mixture itself.**Severe effects after repeated or prolonged exposure**

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

Delta D350 Fast Black Polyurethane Adhesive Component B

Product code: D350 Component B

Page 5 of 7

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No information available.

SECTION 12: Ecological information**12.1. Toxicity**

No data available

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No data available

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Advice on disposal**

Dispose of waste according to applicable legislation. Consult the appropriate local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. According to EAKV, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Control report for waste code/ waste marking according to EAKV:

Waste disposal number of waste from residues/unused products

160306 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; off-specification batches and unused products; organic wastes other than those mentioned in 16 03 05

Waste disposal number of used product

160306 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; off-specification batches and unused products; organic wastes other than those mentioned in 16 03 05

Waste disposal number of contaminated packaging

150106 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); mixed packaging

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)****14.1. UN number:** Not restricted**14.2. UN proper shipping name:** Not restricted**14.3. Transport hazard class(es):** Not restricted**14.4. Packing group:** Not restricted**Inland waterways transport (ADN)**

Delta D350 Fast Black Polyurethane Adhesive Component B

Product code: D350 Component B

Page 6 of 7

14.1. UN number:	Not restricted
14.2. UN proper shipping name:	Not restricted
14.3. Transport hazard class(es):	Not restricted
14.4. Packing group:	Not restricted

Marine transport (IMDG)

14.1. UN number:	Not restricted
14.2. UN proper shipping name:	Not restricted
14.3. Transport hazard class(es):	Not restricted
14.4. Packing group:	Not restricted

Air transport (ICAO)

14.1. UN number:	Not restricted
14.2. UN proper shipping name:	Not restricted
14.3. Transport hazard class(es):	Not restricted
14.4. Packing group:	Not restricted

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Not restricted

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not restricted

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

2010/75/EU (VOC):	No information available.
2004/42/EC (VOC):	No information available.

Additional information

This mixture is classified as not hazardous according to Regulation (EC) 1272/2008 [GHS].
Not subject to 96/82/EC

National regulatory information**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

Rev. 1,00, 07.05.2015, Initial release

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association

Delta D350 Fast Black Polyurethane Adhesive Component B

Product code: D350 Component B

Page 7 of 7

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organization
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
NOAEL: No observed adverse effect level

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)