

DA508 LOCK AND SEAL ADHESIVE

Page 1 Issued: 18/06/2013 Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product name:DA508 LOCK AND SEAL ADHESIVEProduct code:DA508Company name:Delta Adhesives LimitedUnits 39-41, Claycliffe Business ParkCannon Way, Barugh GreenBarnsleySouth YorkshireS75 1JUUnited KingdomTel: +44 (0) 1226 381571Fax: +44 (0) 1226 381722Emergency tel: +44 (0)7729 773555 (Office Hours Only)Email: info@delta-adhesives.co.uk

2. HAZARDS IDENTIFICATION

Classification under CHIP:	Irritating to eyes, respiratory system and skin. May cause sensitisation by
	skin contact.
Workplace exposure limit:	This substance does not have a workplace exposure limit.
PBT:	This substance is not identified as a PBT substance.
Directive 1999/45/EC:	This mixture meets the criteria for classification as dangerous in accordance
	with Directive 1999/45/EC.

3. COMPOSITION / INFORMATION ON INGREDIENTS

 Hazardous ingredients:
 2-HYDROXYPROPYL METHACRYLATE 50-70%

 EINECS:
 213-090-3
 CAS:
 923-26-2

 [Xi]
 R36;
 [Sens.]
 R43

 •
 2,2-BIS(ACRYLOYLOXYMETHYL)BUTYL ACRYLATE 10-30%

 EINECS:
 239-701-3
 CAS:
 15625-89-5

 [Xi]
 R36/38;
 [Sens.]
 R43

 •
 CUMENE HYDROPEROXIDE 1-10%

 EINECS:
 201-524-7
 CAS:
 80-15-9

 [O]
 R7;
 [Xn]
 R21/22;
 [T]
 R23;
 [C]
 R34;
 [Xn]
 R48/20/22;
 [N]
 R51/53

4. FIRST AID MEASURES

Skin contact:	Remove all contaminated clothes and footwear immediately unless stuck to	
	skin. Wash immediately with plenty of soap and water.	
Eye contact:	Bathe the eye with running water for 15 minutes. Consult a doctor.	
Ingestion:	Do not induce vomiting. Give 1 cup of water to drink every 10 minutes.	
	Consult a doctor.	

DA508 LOCK AND SEAL ADHESIVE

Page 2

Inhalation:	Remove casualty from exposure ensuring one's own safety whilst doing so.
	Consult a doctor.
5. FIRE-FIGHTING MEASU	JRES
Extinguishing media:	Alcohol resistant foam. Dry chemical powder. Carbon dioxide. Do not use
	water Jet
Exposure hazards:	In combustion emits toxic fumes. Explosive.
Protection of fire-fighters:	Wear self-contained breathing apparatus. Wear protective clothing to prevent
	contact with skin and eyes.
6. ACCIDENTAL RELEAS	E MEASURES
Personal precautions:	Refer to section 8 of SDS for personal protection details. If outside do not
	approach from downwind. If outside keep bystanders upwind and away from
	danger point. Mark out the contaminated area with signs and prevent access
	to unauthorised personnel. Turn leaking containers leak-side up to prevent
	the escape of liquid.
Environmental precautions:	Do not discharge into drains or rivers. Contain the spillage using bunding.
Clean-up procedures:	Absorb into dry earth or sand. Transfer to a closable, labelled salvage
	container for disposal by an appropriate method.
7. HANDLING AND STOR	AGE
Handling requirements:	Avoid direct contact with the substance. Ensure there is sufficient ventilation
	of the area. Do not handle in a confined space. Avoid the formation or spread
	of mists in the air.
Storage conditions:	Store in cool, well ventilated area. Keep container tightly closed.
Suitable packaging:	Must only be kept in original packaging.
8. EXPOSURE CONTROL	S / PERSONAL PROTECTION
Engineering measures:	Ensure there is sufficient ventilation of the area.
	Self-contained breathing apparatus must be available in case of emergency.
	Protective gloves.
Eye protection:	Safety glasses. Ensure eye bath is to hand.
Skin protection:	Protective clothing.
9. PHYSICAL AND CHEM	ICAL PROPERTIES
State:	Liquid
Colour:	
Odour:	Characteristic odour
Oxidising:	Non-oxidising (by EC criteria)

- Solubility in water: Slightly soluble
 - Viscosity: Viscous

Issued: 18/06/2013

SAFETY DATA SHEET

DA508 LOCK AND SEAL ADHESIVE

Page 3

Kinematic visc. 40°C (mm ² /s):	2250cps
Viscosity test method:	Brookfield (cps)
Boiling point/range°C:	N/A
Melting point/range°C:	N/A
Flash point°C:	> 100
Part.coeff. n-octanol/water:	< 3
Autoflammability°C:	N/A
Vapour pressure:	0.1 mmHg 20C
Relative density:	1.08
pH:	3 - 5

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Heat.

Materials to avoid: Oxidising agents. Acids.

Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Acute effects: Irritating to eyes, respiratory system and skin.

Sensitisation: May cause sensitisation by skin contact.

11. TOXICOLOGICAL INFORMATION (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Exposure may cause coughing or wheezing.

12. ECOLOGICAL INFORMATION

Mobility: Readily absorbed into soil.

Persistence and degradability: No data available.

Bioaccumulative potential: No data available.

Other adverse effects: No data available.

PBT identification: This substance is not identified as a PBT substance.

13. DISPOSAL CONSIDERATIONS

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION

DA508 LOCK AND SEAL ADHESIVE

ADR / RID		
Αυκ / ΚΙυ		
UN no:	None	
Shipping name:	Not hazardous for transport	
Labelling:	None	
IMDG / IMO		
Labelling:	None - Not hazardous for transport	
IATA / ICAO		
Labelling:	None - Not hazardous for transport	
15. REGULATORY INFORMATION (CHIP)		
Hazard symbols:	Irritant.	
Risk phrases:	R36/37/38: Irritating to eyes, respiratory system and skin.	
·	R43: May cause sensitisation by skin contact.	
Safety phrases:	S2: Keep out of the reach of children.	
	S24: Avoid contact with skin.	
	S37: Wear suitable gloves.	
	S46: If swallowed, seek medical advice immediately and show this container	
	or label.	
Haz. ingredients (label):	2-HYDROXYPROPYL METHACRYLATE; 2,2-BIS(ACRYLOYLOXYMETHYL)BUTYL	
	ACRYLATE; CUMENE HYDROPEROXIDE	
Note:	The regulatory information given above only indicates the principal	
	regulations specifically applicable to the product described in the safety data	
	sheet. The user's attention is drawn to the possible existence of additional	
	provisions which complete these regulations. Refer to all applicable national,	
	international and local regulations or provisions.	
16. OTHER INFORMATION		
Other information:	This safety data sheet is prepared in accordance with Regulation (EC) No	
	1907/2006.	

* indicates text in the SDS which has changed since the last revision.

Risk phrases used in s.3: R36: Irritating to eyes.

Page 4

DA508 LOCK AND SEAL ADHESIVE

Page 5

R43: May cause sensitisation by skin contact.R36/38: Irritating to eyes and skin.R7: May cause fire.R21/22: Harmful in contact with skin and if swallowed.R23: Toxic by inhalation.R34: Causes burns.R48/20/22: Harmful: danger of serious damage to health by prolongedexposure through inhalation and if swallowed.R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in
the aquatic environment.Legal disclaimer:The above information is believed to be correct but does not purport to be all
inclusive and shall be used only as a guide. This company shall not be held
liable for any damage resulting from handling or from contact with the above
product.