

**DELTA D377 Thread Sealant**

Product code: D377

Page 1 of 10

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

D377 Thread Sealant

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Adhesives, sealants

**Uses advised against**

any non-intended use.

**1.3. Details of the supplier of the safety data sheet**

Company name: Delta Adhesives Limited  
Place: Units 39-40 Claycliffe Business Park, Barnsley, S75 1JU, United Kingdom  
Telephone: +44 (0)1226 381571  
Internet: [www.delta-adhesives.co.uk](http://www.delta-adhesives.co.uk)  
Responsible Department: sales@delta-adhesives.co.uk

**1.4. Emergency telephone number:** +44 (0)1226 381571 (Mon-Fri, 08:00-16:00)

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture**

Indications of danger: Xi - Irritant, N - Dangerous for the environment

R phrases:

Irritating to eyes, respiratory system and skin.

May cause sensitisation by skin contact.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**GHS classification**

Hazard categories:

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Respiratory/skin sensitization: Skin Sens. 1

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

May cause respiratory irritation.

Toxic to aquatic life with long lasting effects.

**2.2. Label elements****Hazardous components which must be listed on the label**

Polyglycol dimethacrylate

dodecyl methacrylate

tetradecyl methacrylate

Signal word: Warning

Pictograms: GHS07-GHS09

**DELTA D377 Thread Sealant**

Product code: D377

Page 2 of 10

**Hazard statements**

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H411	Toxic to aquatic life with long lasting effects.

**Precautionary statements**

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P312	Call a POISON CENTER/doctor if you feel unwell.
P501	Dispose of contents/container to in accordance with official regulations.

**2.3. Other hazards**

No information available.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Hazardous components**

EC No	Chemical name	Quantity
CAS No	Classification	
Index No	GHS classification	
REACH No		
	Polyglycol dimethacrylate	40 - < 45 %
25852-47-5	R43-52-53	
	Skin Sens. 1, Aquatic Chronic 3; H317 H412	
205-570-6	dodecyl methacrylate	10 - < 15 %
142-90-5	Xi - Irritant, N - Dangerous for the environment R36/37/38-50-53	
607-247-00-9	Eye Irrit. 2, STOT SE 3, Skin Irrit. 2, Aquatic Acute 1, Aquatic Chronic 1; H319 H335 H315 H400 H410	
219-835-9	tetradecyl methacrylate	5 - < 10 %
2549-53-3	Xi - Irritant R36/38-43	
	Eye Irrit. 2, Skin Irrit. 2, Skin Sens. 1; H319 H315 H317	
204-055-3	2'-Phenylacetohydrazide	< 1 %
114-83-0	T - Toxic, Xi - Irritant R25-36/37/38-43	
	Acute Tox. 3, Eye Irrit. 2, STOT SE 3, Skin Irrit. 2, Skin Sens. 1; H301 H319 H335 H315 H317	

Full text of R and H phrases: see Section 16.

**Further Information**

Product does not contain listed SVHC substances.

**SECTION 4: First aid measures**

**DELTA D377 Thread Sealant**

Product code: D377

Page 3 of 10

**4.1. Description of first aid measures****General information**

In case of accident or if you feel unwell, seek medical advice immediately (show safety data sheet if possible).

**After inhalation**

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

**After contact with skin**

After contact with skin, wash immediately with plenty of water and soap. If skin irritation or rash occurs: Get medical advice/attention.

**After contact with eyes**

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

**After ingestion**

Do not induce vomiting. Rinse mouth thoroughly with water. Let water be swallowed in little sips (dilution effect). Never give anything by mouth to an unconscious person or a person with cramps. Call a POISON CENTER or doctor/physician.

**4.2. Most important symptoms and effects, both acute and delayed**

No information available.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Dry extinguishing powder. Foam. Water spray. Carbon dioxide (CO<sub>2</sub>).

**Unsuitable extinguishing media**

High power water jet.

**5.2. Special hazards arising from the substance or mixture**

Can be released in case of fire: Carbon monoxide. Carbon dioxide (CO<sub>2</sub>). Nitrogen oxides (NO<sub>x</sub>).

**5.3. Advice for firefighters**

Wear a self-contained breathing apparatus and chemical resistant suit. In case of fire and/or explosion do not breathe fumes.

**Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Use water spray/stream to protect personnel and to cool endangered containers.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Provide adequate ventilation.

Do not breathe gas/vapour/spray. Avoid contact with skin, eye and clothing.

Wear personal protection equipment. (refer to chapter 8)

**6.2. Environmental precautions**

Do not empty into drains or the aquatic environment. Prevent spreading over great surfaces (e.g. by damming or installing oil booms). In case of leakage into waters, ground or the drainage system, the appropriate authorities must be informed.

**6.3. Methods and material for containment and cleaning up**

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Ventilate affected area.

**DELTA D377 Thread Sealant**

Product code: D377

Page 4 of 10

Treat the assimilated material according to the section on waste disposal.  
Clear contaminated area thoroughly.

**6.4. Reference to other sections**

See protective measures under point 7 and 8.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Provide adequate ventilation.  
Wear suitable protective clothing. ( Refer to chapter 8. )

**Advice on protection against fire and explosion**

Usual measures for fire prevention.

**Further information on handling**

Do not breathe gas/vapour/spray. Avoid contact with skin, eye and clothing.  
General protection and hygiene measures: refer to chapter 8

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place. Keep container dry.

**Advice on storage compatibility**

Do not store together with: Explosives. Oxidizing solids. Oxidizing liquids. Radioactive substances.  
Infectious substances.

**Further information on storage conditions**

Protect against: Light. UV-radiation/sunlight. heat. cooling. moisture.

**7.3. Specific end use(s)**

No information available.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Additional advice on limit values**

To date, no national limit values exist.

**8.2. Exposure controls****Appropriate engineering controls**

In case of open handling, use devices with built-in suction where possible. If suction of the immediate vicinity is impossible or insufficient, adequate airing of the working place must be ensured.

**Protective and hygiene measures**

Always close containers tightly after the removal of product. Do not eat, drink, smoke or sneeze at the workplace. Wash hands before breaks and at the end of work. Remove contaminated clothing immediately and dispose off safely. Wash contaminated clothing prior to re-use. Used working clothes should not be used outside the work area. Street clothing should be stored separately from work clothing. Protect skin by using skin protective cream.

**Eye/face protection**

Suitable eye protection: Tightly sealed safety glasses. DIN EN 166

**Hand protection**

Pull-over gloves of rubber. DIN EN 374

**DELTA D377 Thread Sealant**

Product code: D377

Page 5 of 10

Suitable material:

(Breakthrough time  $\geq$  480 min, penetration time (maximum wearing period): 160 min)

CR (polychloroprenes, Chloroprene rubber). (0,5 mm)

FKM (fluororubber). (0,4 mm)

Butyl rubber. (0,5 mm)

Before using check leak tightness / impermeability. In case of reutilization, clean gloves before taking off and store in well-aired place.

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

**Skin protection**

Suitable protection of the body: Lab apron.

**Respiratory protection**Respiratory protection required in case of:  
insufficient ventilation.

Generation/formation of aerosols

Generation/formation of mist

Suitable respiratory protective equipment: Combination filter device (DIN EN 141).. Type : A / P2/P3

The filter class must be suitable for the maximum contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, closed-circuit breathing apparatus must be used!

**Environmental exposure controls**

Do not empty into drains or the aquatic environment.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	Yellow
Odour:	characteristic

**Test method**

pH-Value: not determined

**Changes in the physical state**

Melting point: not determined

Initial boiling point and boiling range: not determined

Flash point: not determined

**Explosive properties**

none/none

Lower explosion limits: not determined

Upper explosion limits: not determined

**Oxidizing properties**

none/none

Vapour pressure: not determined

Density: not determined

Viscosity / dynamic: not determined

**9.2. Other information**

No information available.

**SECTION 10: Stability and reactivity**

**DELTA D377 Thread Sealant**

Product code: D377

Page 6 of 10

**10.1. Reactivity**

No information available.

**10.2. Chemical stability**

Stable under normal storage and handling conditions.

**10.3. Possibility of hazardous reactions**

No information available.

**10.4. Conditions to avoid**

Protect against: Light. UV-radiation/sunlight. heat. cooling. moisture.

**10.5. Incompatible materials**

Materials to avoid: Strong acid. Oxidizing agents, strong. Alkalis (alkalis), concentrated.

**10.6. Hazardous decomposition products**Can be released in case of fire: Carbon monoxide. Carbon dioxide (CO<sub>2</sub>). Nitrogen oxides (NO<sub>x</sub>).**SECTION 11: Toxicological information****11.1. Information on toxicological effects****Toxicokinetics, metabolism and distribution**

No information available.

**Acute toxicity**

Based on available data, the classification criteria are not met.

**Acute toxicity**

CAS No	Chemical name	Exposure routes	Method	Dose	Species	Source
114-83-0	2'-Phenylacetohydrazide	oral	LD50	270 mg/kg	Mouse.	

**Irritation and corrosivity**

Causes skin irritation.

Causes serious eye irritation.

**Sensitising effects**

May cause an allergic skin reaction. (Polyglycol dimethacrylate), (tetradecyl methacrylate), (2'-Phenylacetohydrazide)

Respiratory or skin sensitisation:

People who suffer from skins problems, asthma, allergies, chronic or recurring respiratory illnesses must not be deployed in processes, which use this substance.

**STOT-single exposure**

May cause respiratory irritation. (dodecyl methacrylate), (2'-Phenylacetohydrazide)

**Severe effects after repeated or prolonged exposure**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Specific effects in experiment on an animal**

No information available.

**SECTION 12: Ecological information****12.1. Toxicity**

**DELTA D377 Thread Sealant**

Product code: D377

Page 7 of 10

No data available

**12.2. Persistence and degradability**

No data available

**12.3. Bioaccumulative potential****Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
142-90-5	dodecyl methacrylate	6,68
2549-53-3	tetradecyl methacrylate	7,66

**12.4. Mobility in soil**

No data available

**12.5. Results of PBT and vPvB assessment**

No data available

**12.6. Other adverse effects**

No data available

**Further information**

Do not empty into drains or the aquatic environment.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Advice on disposal**

Waste disposal according to official state regulations. Consult the local waste disposal expert about waste disposal. Cleaned containers may be recycled.

**Waste disposal number of waste from residues/unused products**

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other dangerous substances  
Classified as hazardous waste.

**Waste disposal number of used product**

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other dangerous substances  
Classified as hazardous waste.

**Waste disposal number of contaminated packaging**

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by dangerous substances  
Classified as hazardous waste.

**Contaminated packaging**

Handle contaminated packaging in the same way as the substance itself.

**SECTION 14: Transport information****Land transport (ADR/RID)****14.1. UN number:**

UN 3082

**14.2. UN proper shipping name:**ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(dodecyl methacrylate)**14.3. Transport hazard class(es):**

9

**DELTA D377 Thread Sealant**

Product code: D377

Page 8 of 10

**14.4. Packing group:**

III

Hazard label:

9



Classification code:

M6

Special Provisions:

274 335 601

Limited quantity:

5 L

Transport category:

3

Hazard No:

90

Tunnel restriction code:

E

**Other applicable information (land transport)**

Excepted quantity: E1

**Inland waterways transport (ADN)****14.1. UN number:**

UN 3082

**14.2. UN proper shipping name:**ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(dodecyl methacrylate)**14.3. Transport hazard class(es):**

9

**14.4. Packing group:**

III

Hazard label:

9



Classification code:

M6

Special Provisions:

274 335 601

Limited quantity:

5 L

**Other applicable information (inland waterways transport)**

Excepted quantity: E1

**Marine transport (IMDG)****14.1. UN number:**

UN 3082

**14.2. UN proper shipping name:**ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(dodecyl methacrylate)**14.3. Transport hazard class(es):**

9

**14.4. Packing group:**

III

Hazard label:

9



Marine pollutant:

YES

Special Provisions:

274, 335

Limited quantity:

5 L

EmS:

F-A, S-F

**Other applicable information (marine transport)**

Excepted quantity: E1

**Air transport (ICAO)****14.1. UN number:**

UN 3082



**DELTA D377 Thread Sealant**

Product code: D377

Page 9 of 10

**14.2. UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(dodecyl methacrylate)

**14.3. Transport hazard class(es):** 9

**14.4. Packing group:** III

Hazard label: 9



Special Provisions: A97 A158

Limited quantity Passenger: 30 kg G

IATA-packing instructions - Passenger: 964

IATA-max. quantity - Passenger: 450 L

IATA-packing instructions - Cargo: 964

IATA-max. quantity - Cargo: 450 L

**Other applicable information (air transport)**

Passenger-LQ: Y964

Excepted quantity: E1

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: yes



Danger releasing substance: dodecyl methacrylate

**14.6. Special precautions for user**

refer to chapter 6-8

**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

irrelevant

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

1999/13/EC (VOC): No information available. VOC Directive 2004/42/EC: No information available.

**Additional information**

The preparation is dangerous in the sense of Directive 1999/45/EC.

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

Regulation 96/82/EC for danger control following severe accidents with dangerous substances: Appendix I, Part 2, No 9ii, siehe StörfallVO (Seveso II).

REACH 1907/2006 Appendix XVII, No 3

**National regulatory information**

Employment restrictions: Observe employment restrictions for young people.

Water contaminating class (D): 2 - water contaminating

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information****Changes**

Rev. 1,00, 16.12.2014, Initial release

**DELTA D377 Thread Sealant**

Product code: D377

Page 10 of 10

**Abbreviations and acronyms**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)  
ICAO: International Civil Aviation Organization  
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)  
GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
NOAEL: No observed adverse effect level

**Full text of R phrases referred to under Sections 2 and 3**

25 Toxic if swallowed.  
36/37/38 Irritating to eyes, respiratory system and skin.  
36/38 Irritating to eyes and skin.  
43 May cause sensitisation by skin contact.  
50 Very toxic to aquatic organisms.  
51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
52 Harmful to aquatic organisms.  
53 May cause long-term adverse effects in the aquatic environment.

**Full text of H statements referred to under Sections 2 and 3**

H301 Toxic if swallowed.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H411 Toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*