

TECHNICAL DATA	MOVEMENT ACCOMODATION	+ or - 20%
	SKINNING TIME	5 mins @ 20°C
	CURE TIME	3mm per 24 hours
	HARDNESS SHORE A:	20 - 25
	SHRINKAGE	<3%
	SERVICE TEMPERATURE RESISTANCE	-50° to 300°C
	APPLICATION TEMPERATURE	+5°C to +40°C
	TENSILE STRENGTH	1.0 MPa
	STRESS	0.3 MPa
	SPECIFIC GRAVITY	1.02 - 1.05
	MINIMUM JOINT WIDTH	6mm
	MAXIMUM JOINT WIDTH	30mm
	JOINT RATIO	Maximum depth 50% of joint width
	COVERAGE	@ 10 linear meters 9 x 9mm fillet joint
	COLOUR	Black
SHELF LIFE	12 months when stored in unopened packaging @ +5° to +25°C	

PACKAGING • Self applying 200ml pressure pack.

HEALTH AND SAFETY • Refer to the relevant Material Safety Data Sheet (MSDS).

LEGAL NOTICE

The data contained within this Technical Data Sheet is furnished for information only and is believed to be reliable at the time of issue. We cannot assume responsibility for results obtained by others over whose methods we have no control. It is the responsibility of the customer to determine the products suitability for use. Delta Adhesives Limited accepts no liability arising out of the use of this information or the product described herein.

HODGHVLHVLPPLHGLVODOLIIHVLHV3DUN□
DRDDUHHHDUVVOH6RRUNVLUH6□
HOHPDLOVDOHVGHODDGHVLHVVRN